



Aqueous Parts Washer Model 175-E

10250 SE Mather Rd. Clackamas, OR 97015 800-332-1590 www.hvdro-blast.com



SMART QUESTIONS

1. How do I cut parts cleaning / preparation time before my next step in the parts cleaning process? 2. How do I minimize parts washing operator expense?

3. How can I clean my parts without using harmful solvents? 4. How can I avoid expensive waste-water disposal cost and potential fines?

Washing parts can be TIME AND LABOR intensive. A Hydro-Blast aqueous parts washer quickly cleans parts saving employee time and labor thus increasing company productivity and profitability. Simply load the

HEAVY EQ · TUBINE · LARGE PARTS MANUFACTURING Eliminate the use of Harmful Solvents!

| | STANDARD FEATURES: EA Load Height Turntable Diameter Load Capacity kW of Heat Pump HP Power Req. (240V, 1p, 182a Dimensions W x 66" D x 5 Flow Rate Spray Bar Pressure # of Spray Jets Low Water Shut-Off 7 Day Mechanical Timer | 60" 44" 2,500 lb 30 kW 7.5 HP imp) (240 | s. V, 3p 3" (Ir | All Hydro-Blast cabinet style aqueous parts washers include front and top doors for easy access, low water shut-off, a 7 day mechanical heat timer, & digital temp readout. b, 104amp) (480V, 3p, 52amp) ncludes Stack Height) Hydro-Blast, Inc. uses a heavy- duty industrial design for some of the highest load capacities in the |
|----|---|--|-----------------------|---|
| | Turn Table Jog Switch on Co Oil Skimmer Wheel 60 Min. Spring Wound Wash Turntable Basket Turntable with Integrated Pa Side and Top Door Access Heavy Duty 11 Gage Constr High Impact Zero Degree Sp Safety Screen to Catch Drop Cast Iron Vertical Sealless F Fork Lift Accessible Foot Lifting Eyes for Easy Hoistin Shipping Weight (Approx.) | n on Control Panel I Wash Timer ted Parts Tree ccess Construction ree Spray h Dropped Parts lless Pump bot Hoisting w/crane rox.) 2,950 lbs. | | Parts Cleaning industry. Each mild steel unit is powder coated for chip, scratch and corrosive resistance. Each Parts Washer is engineered for trouble free maintenance and operation. Seams are welded to be water tight, and there are no door gaskets to leak or wear out. Our small footprint allows you to place a large capacity washer in a limited space. Stainless steel and many other options are also available. |
|) | OPTIONS & UPGRADES: Electronic Freshwater Fill | Bag F | | S HEATED 175-G AVAILABLE |
| st | Small Parts Baskets Double Tier Turntable | | | |

Digital Controls and Readouts Pump Upgrades Stainless Steel Construction **Evaporation System**



parts, close the door, set the timer and parts are cleaned automatically. Employee's morale usually improves when there are no more sore cracked hands and hazardous fumes caused by solvent washing. MONEY savings are also generated by reduced hauling costs, insurance, and potential fines associated with hazardous chemical spills. AN AQUEOUS PARTS WASHER WILL USUALLY PAY FOR ITSELF IN LESS THAN A YEAR. HYDRO-BLAST WORKS!

Dirty parts are loaded into the Model 175 Hydro-Blast aqueous washer and sprayed with hot water and biodegradable detergent. The high flow of wash solution maintains full impact with zero degree spray jets. The parts heat to wash temperature and quickly release contaminants. Parts are usually clean and ready for use in 10 to 15 minutes or less!



Environmental Solutions by Hydro-Blast Inc.

